

| | Standard | Result |
|--|--|--|
| Size | ISO 24342 | See separate table |
| Thickness | ISO 24346 | 3.0 mm |
| Wear layer | ISO 24340 | 0.7 mm |
| Surface treatment | | K-Guard+ PU coating |
| Warranty¹ | Commercial Domestic | 20 years wear Lifetime wear |
| Bevelled edge | | Standard |
| Standards | EN 649/EN ISO 10582 ASTM F1700 | Pass Pass |
| Classification | ISO 10874 - Commercial ISO 10874 - Domestic | 34: Commercial very heavy 23: Domestic heavy |
| Reaction to fire | AS/NZS 9239.1:2003 | CRF: Smoke value: Hand Crafted Wood 7.1 kW/m ² 121% min Oak Royale 6.4 kW/m ² 114% min Oak Premier 8.5 kW/m ² 177% min Parquet 8.5 kW/m ² 220% min |
| Staining resistance | EN ISO 26987/EN 423 ASTM F925 | Excellent Pass |
| Light fastness | ISO 105-B02 ASTM F1515 | Pass (≥ 6) Pass (< 8) |
| Abrasion resistance | EN 660-2 ISO 10582 ASTM D3884 | Group T Type 1 Pass |
| Flexibility | ISO 24344 | Pass |
| Dimensional stability | EN 434/ISO 23999 ASTM F2199 | Pass (≤ 0.25%) Pass |
| Acoustic impact noise reduction² | EN ISO 717-2/EN ISO 140-8 | ΔL _w = 2 dB |
| Electrical behaviour body voltage | EN 1815 | Pass |
| Indentation - residual | EN 433/ISO 24343-1 ASTM F1914 | Pass (≤ 0.1 mm) Pass (< 8%) |
| Castor chair continuous use | EN 425/ISO 4918 | Pass |
| Thermal resistance | ISO 8302 | 0.0147 m ² K/W Suitable for underfloor heating. Max 27°C |
| Slip resistance³ | AS/NZS 4586:2013 | See separate table |
| Adhesive | General use: High temperature: | Karndean Mega-Bond Karndean 8000 2-part Polyurethane |
| Environmental | GBCA/NZGBC GreenStar Rating System Floorscore SCS-EC10.3-2014 v4.0 Indoor Air Comfort Environmental Product Declaration NSF/ANSI 332 ISO 14001 / ISO 9001 | GreenRate Level 'A'; LCA Silver Plus; Best Practice PVC Indoor air quality certified; Compliant low emitting VOC emissions. Gold certification Compliant low emitting VOC emissions. Product-specific Type III EPD (products with external third-party verification) Sustainability Assessment for Resilient Floor Coverings; Conformant product Manufactured to quality and environment management systems standards |
| Recycling | | Suitable |
| Phthalate free | | Yes |

¹ Subject to terms. Please see our website.

² Result is Ln,w = 58 dB when installed on Regupol 4515 acoustic underlay.

³ Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

Every Karndean range and format meets our certification policy standards - be sure to verify the current certification status

For more information:

Call: 1800 33 11 70
Email: customerservice@karndean.com.au
Visit: www.karndeancommercial.com or www.karndean.com

Nov 24



| Product Code | Size | | Box Quantity | | Slip Resistance Oil-Wet Ramp |
|--------------|----------------|----------|----------------|------------|---------------------------------|
| | mm | inches | m ² | Pieces | |
| AP01 | 228.6 x 76.2 | 9" x 3" | 3.345 | 192 Planks | R9 |
| AP02 | 228.6 x 76.2 | 9" x 3" | 3.345 | 192 Planks | R9 |
| AP03 | 228.6 x 76.2 | 9" x 3" | 3.345 | 192 Planks | R9 |
| EW01 | 914.4 x 152.4 | 36" x 6" | 3.345 | 24 Planks | R9 |
| EW02 | 914.4 x 152.4 | 36" x 6" | 3.345 | 24 Planks | R9 |
| EW03 | 914.4 x 152.4 | 36" x 6" | 3.345 | 24 Planks | R9 |
| HC01 | 914.4 x 152.4 | 36" x 6" | 3.345 | 24 Planks | R9 |
| HC02 | 914.4 x 152.4 | 36" x 6" | 3.345 | 24 Planks | R9 |
| HC03 | 914.4 x 152.4 | 36" x 6" | 3.345 | 24 Planks | R9 |
| HC04 | 914.4 x 152.4 | 36" x 6" | 3.345 | 24 Planks | R9 |
| HC05 | 914.4 x 152.4 | 36" x 6" | 3.345 | 24 Planks | R9 |
| HC06 | 914.4 x 152.4 | 36" x 6" | 3.345 | 24 Planks | R9 |
| RL01 | 1219.2 x 177.8 | 48" x 7" | 3.252 | 15 Planks | R9 |
| RL02 | 1219.2 x 177.8 | 48" x 7" | 3.252 | 15 Planks | R9 |
| RL03 | 1219.2 x 177.8 | 48" x 7" | 3.252 | 15 Planks | R9 |
| RL04 | 1219.2 x 177.8 | 48" x 7" | 3.252 | 15 Planks | R9 |

Wood Designs