

	Standard	Result
Size	ISO 24342	See separate table
Thickness	ISO 24346	2.0 mm
Wear layer	ISO 24340	0.3 mm
Surface treatment		K-Guard+ PU coating
Warranty ¹	Commercial Domestic	10 years light commercial wear Lifetime wear
Bevelled edge		No
Standards	EN 649/EN ISO 10582 ASTM F1700	Pass Pass
Classification	ISO 10874 - Commercial ISO 10874 - Domestic	31: Commercial moderate 23: Domestic heavy
Reaction to fire	AS/NZS ISO 9239.1:2010	CRF: 8.1 kW/m ² Smoke value: 42% min.
Staining resistance	EN ISO 26987/EN 423 ASTM F925	Excellent Pass
Light fastness	ISO 105-B02 ASTM F1515	Pass (≥ 6) Pass (< 8)
Abrasion resistance	EN 660-2 ISO 10582 ASTM D3884	Group T Type 1 Pass
Flexibility	ISO 24344	Pass
Dimensional stability	EN 434/ISO 23999 ASTM F2199	Pass (≤ 0.25%) Pass
Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL _w = 1 dB
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433/ISO 24343-1 ASTM F1914	Pass (≤ 0.1 mm) Pass (< 8%)
Castor chair continuous use	EN 425/ISO 4918	Pass
Thermal resistance	ISO 8302	0.0100 m ² K/W Suitable for underfloor heating. Max 27°C
Slip resistance ²	AS/NZS 4586:2013	See separate table
Adhesive	General use: High temperature:	Karndean Mega-Bond Karndean 8000 2-part Polyurethane
Environmental	Floorscore SCS-EC10.3-2014 v4.0 Indoor Air Comfort Environmental Product Declaration NSF/ANSI 332 ISO 14001 / ISO 9001	Indoor air quality certified; Compliant low emitting VOC emissions. Gold certification Compliant low emitting VOC emissions. Product-specific Type III EPD (products with external third-party verification) Sustainability Assessment for Resilient Floor Coverings; Conformant product Manufactured to quality and environment management systems standards
Recycling		Suitable
Phthalate free		Yes

¹ Subject to terms. Please see our website.

² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

Every Karndean range and format meets our certification policy standards - be sure to verify the current certification status

For more information:

Call: 1800 33 11 70
Email: customerservice@karndean.com.au
Visit: www.karndeancommercial.com or www.karndean.com

Nov 24



SUPPORTING A CIRCULAR FUTURE FOR FLOORING



	Product Code	Size		Box Quantity		Slip Resistance Oil-Wet Ramp
		mm	inches	m ²	Pieces	
Wood Designs	KP94-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP95-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP96-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP99-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP104-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP105-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP138-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP141-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP143-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP144-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP146-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP147-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP149-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP150-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP153-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
KP157-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10	
Stone Designs	ST16	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R9
	ST17	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R9
	ST19	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R9
	ST20	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R9
	ST21	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R9
	ST22	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R9