

	Standard	Result
Size	ISO 24342	See separate table
Thickness	ISO 24346	2.5 mm
Wear layer	ISO 24340	0.5 mm
Surface treatment		K-Guard+ PU coating
Warranty ¹	Commercial Domestic	15 years wear Lifetime wear
Bevelled edge		Micro
Standards	ASTM F1700	Pass
Classification	ISO 10874 - Commercial ISO 10874 - Domestic	33: Commercial heavy 23: Domestic heavy
Reaction to fire	AS/NZS 9239.1:2010	CRF: > 11 kW/m ² Smoke value: 93% min.
Staining resistance	EN ISO 26987/EN 423 ASTM F925	Excellent Pass
Light fastness	ISO 105-B02 ASTM F1515	Pass (≥ 7) Pass (< 8)
Abrasion resistance	EN 660-2 ISO 10582 ASTM D3884	Group T Type 1 Pass
Flexibility	ISO 24344	Pass
Dimensional stability	EN 434/ISO 23999 ASTM F2199	Pass (≤ 0.25%) Pass
Acoustic impact noise reduction ²	EN ISO 717-2/EN ISO 140-8	ΔL _w = 2 dB
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433/ISO 24343-1 ASTM F1914	Pass (≤ 0.1 mm) Pass (< 8%)
Castor chair continuous use	EN 425/ISO 4918	Pass
Thermal resistance	ISO 8302	0.0097 m ² K/W Suitable for underfloor heating. Max 27°C
Slip resistance ³	AS/NZS 4586:2013	See separate table
Adhesive	General use: High temperature:	Karndean Mega-Bond Karndean 8000 2-part Polyurethane
Environmental	GBCA/NZGBC GreenStar Rating System Floorscore SCS-EC10.3-2014 v4.0 Indoor Air Comfort Environmental Product Declaration NSF/ANSI 332 ISO 14001 / ISO 9001	GreenRate Level 'A'; LCA Silver Plus; Best Practice PVC Indoor air quality certified; Compliant low emitting VOC emissions. Gold certification Compliant low emitting VOC emissions. Product-specific Type III EPD (products with external third-party verification) Sustainability Assessment for Resilient Floor Coverings; Conformant product Manufactured to quality and environment management systems standards
Recycling		Suitable
Phthalate free		Yes

¹ Subject to terms. Please see our website.

² Result is Ln,w = 58 dB when installed on Regupol 4515 acoustic underlay

³ Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

Every Karndean range and format meets our certification policy standards - be sure to verify the current certification status

For more information:

Call: 1800 33 11 70
Email: customerservice@karndean.com.au
Visit: www.karndeancommercial.com or www.karndean.com

Nov 24





	Product Code	Size		Box Quantity		Slip Resistance Oil-Wet Ramp
		mm	inches	m ²	Pieces	
Wood Designs	WP311	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP312	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP313	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP313-SR	914.4 x 152.4	36" x 6"	3.345	24 Planks	R11
	WP315	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP316	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP318	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP318-SR	914.4 x 152.4	36" x 6"	3.345	24 Planks	R11
	WP319	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP319-SR	914.4 x 152.4	36" x 6"	3.345	24 Planks	R11
	WP329	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP329-SR	914.4 x 152.4	36" x 6"	3.345	24 Planks	R11
	WP411	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10
	WP411-SR	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R11
	WP413	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10
	WP414	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10
	WP421	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10
	WP422	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10
WP423	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10	
Stone Designs	SP111	457.2 x 457.2	18" x 18"	3.345	16 Tiles	R10
	SP114	457.2 x 457.2	18" x 18"	3.345	16 Tiles	R10
	SP115	457.2 x 457.2	18" x 18"	3.345	16 Tiles	R10
	SP211	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10
	SP212	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10
	SP213	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10
	SP213-SR	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R11
	SP214	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10
	SP215	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10
	SP216	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10
SP217	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10	