






















	Standard	Result
 Size	ISO 24342	1219.2 mm x 177.8 mm
 Thickness	ISO 24346	3.0 mm
 Wear layer	ISO 24340	0.5 mm
Surface treatment		K-Guard+ PU coating
Warranty¹	Commercial	15 years wear
	Domestic	Lifetime wear
 Bevelled edge		Micro
 Standards	ASTM F1700	Pass
 Classification	ISO 10874 - Commercial	33: Commercial heavy
	ISO 10874 - Domestic	23: Domestic heavy
 Reaction to fire	AS/NZS 9239.1:2010	CRF: 7.3 kW/m ² Smoke value: 124% min.
 Staining resistance	EN ISO 26987/EN 423 ASTM F925	Excellent Pass
 Light fastness	ISO 105-B02 ASTM F1515	Pass (≥ 7) Pass (< 8)
 Abrasion resistance	EN 660-2 ISO 10582 ASTM D3884	Group T Type 1 Pass
 Flexibility	ISO 24344	Pass
 Dimensional stability	EN 434/ISO 23999 ASTM F2199	Pass (≤ 0.25%) Pass
 Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL _w = 4 dB
 Electrical behaviour body voltage	EN 1815	Pass
 Indentation - residual	EN 433/ISO 24343-1 ASTM F1914	Pass (≤ 0.1 mm) Pass (< 8%)
 Castor chair continuous use	EN 425	Pass
 Thermal resistance	ISO 8302	0.0118 m ² K/W Suitable for underfloor heating. Max 27°C
 Slip resistance²	AS/NZS 4586:2013	R10
 Adhesive	General use: High temperature:	Karndean Mega-Bond Karndean 8000 2-part Polyurethane
Environmental	GBCA/NZGBC GreenStar Rating System Floorscore SCS-EC10.3-2014 v4.0 Indoor Air Comfort Environmental Product Declaration NSF/ANSI 332 ISO 14001 / ISO 9001	GreenRate Level 'A'; LCA Silver Plus; Best Practice PVC Indoor air quality certified; Compliant low emitting VOC emissions. Gold certification Compliant low emitting VOC emissions. Product-specific Type III EPD (products with external third-party verification) Sustainability Assessment for Resilient Floor Coverings; Conformant product Manufactured to quality and environment management systems standards
 Recycling		Suitable
 Phthalate free		Yes

¹ Subject to terms. Please see our website.

² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

Every Karndean range and format meets our certification policy standards - be sure to verify the current certification status

For more information: Call: 1800 33 11 70
Email: customerservice@karndean.com.au
Visit: www.karndeancommercial.com or www.karndean.com

Nov 24



Product Code	Size		Box Quantity		Slip Resistance
	mm	inches	m ²	Pieces	Oil-Wet Ramp
VGW81T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW82T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW84T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW85T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW86T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW89T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW103T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW107T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW110T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW111T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW112T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW127T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW128T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW129T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW130T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW131T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW132T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW133T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW134T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW135T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10

Wood Designs