

	Standard	Result
Size	ISO 24342	See separate table
Thickness	ISO 24346	2.5 mm
Wear layer	ISO 24340	0.5 mm
Surface treatment		K-Guard+ PU coating
Warranty ¹	Commercial	15 years wear
	Domestic	Lifetime wear
Bevelled edge		Micro
Standards	ASTM F1700	Pass
Classification	ISO 10874 - Commercial	33: Commercial heavy
	ISO 10874 - Domestic	23: Domestic heavy
Reaction to fire	AS/NZS 9239.1:2010	CRF: > 11 kW/m ² Smoke value: 93% min.
Staining resistance	EN ISO 26987/EN 423	Excellent
	ASTM F925	Pass
Light fastness	ISO 105-B02	Pass (≥ 7)
	ASTM F1515	Pass (< 8)
Abrasion resistance	EN 660-2	Group T
	ISO 10582	Type 1
	ASTM D3884	Pass
Flexibility	ISO 24344	Pass
Dimensional stability	EN 434/ISO 23999	Pass (≤ 0.25%)
	ASTM F2199	Pass
Acoustic impact noise reduction ²	EN ISO 717-2/EN ISO 140-8	ΔL _w = 2 dB
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433/ISO 24343-1	Pass (≤ 0.1 mm)
	ASTM F1914	Pass (< 8%)
Castor chair continuous use	EN 425/ISO 4918	Pass
Thermal resistance	ISO 8302	0.0097 m ² K/W
		Suitable for underfloor heating. Max 27°C
Slip resistance ³	AS/NZS 4586:2013	See separate table
Adhesive	General use:	Karndean Mega-Bond
	High temperature:	Karndean 8000 2-part Polyurethane
Environmental	GBCA/NZGBC GreenStar Rating System	GreenTag Level A; LCA Silver Plus; Best Practice PVC
	Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions.
	Indoor Air Comfort	Gold certification Compliant low emitting VOC emissions.
	Environmental Product Declaration	Product-specific Type III EPD (products with external third-party verification)
	NSF/ANSI 332	Sustainability Assessment for Resilient Floor Coverings; Conformant product
Recycling	ISO 14001 / ISO 9001	Manufactured to quality and environment management systems standards
Phthalate free		Suitable Yes

¹ Subject to terms. Please see our website.

² Result is L_{n,w} = 58 dB when installed on Regupol 4515 acoustic underlay

³ Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

Australia

Call: 1800 33 11 70
Email: customerservice@karndean.com.au
Visit: www.karndean.com

New Zealand

Call: 0800 44 21 01
Email: customerservice@karndean.co.nz
Visit: www.karndean.com

Jun 22



	Product Code	Size		Box Quantity		Slip Resistance
		mm	inches	m ²	Pieces	Oil-Wet Ramp
Wood Designs	WP311	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP312	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP313	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP315	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP316	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP318	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP319	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP329	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP411	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10
	WP411-SRA	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R11
	WP413	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10
	WP414	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10
WP421	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10	
Stone Designs	SP111	457.2 x 457.2	18" x 18"	3.345	16 Tiles	R10
	SP114	457.2 x 457.2	18" x 18"	3.345	16 Tiles	R10
	SP115	457.2 x 457.2	18" x 18"	3.345	16 Tiles	R10
	SP211	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10
	SP212	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10
	SP213	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10
	SP213-SR	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R11
	SP214	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10
	SP215	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10
	SP216	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10
SP217	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10	