









	Standard	Result
 Size	EN ISO 24342	Various
 Thickness	EN ISO 24346	2.5 mm
 Wear layer	EN ISO 24340	0.55mm
Surface treatment		K-Guard+ PU coating
 Guarantee¹	Light industrial	15 years
	Commercial	15 years
	Residential	Lifetime guarantee
 Slip resistance²	DIN 51130 EN 13893	See individual technical data sheet for details
 Light Reflectance Value (LRV)	BS 8493:2008+A1:2010	See separate table
 Recycling		Suitable
 Phthalate free		Yes

¹ Subject to terms. Please see our website.

² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

	Product Code	LRV
Solid Colours	V11	41
	V12	21
	V13	24
	V14	52
	V15	36
	V16	13
	V17	29
	V18	12
	V19	24
	V20	71
Stone Designs	SP111	66
	SP115	8

See our Opus and Solid colour technical data sheet for comprehensive technical information.

For more information:

UK: 01386 820104 | ROI: 01 6569887

Email: commercial@karndean.co.uk

Visit: www.karndean.com

