






















	Standard	Result
 Size	EN ISO 24342	See separate table
 Thickness	ISO 24346	8.0 mm
 Wear layer	ISO 24340	0.55mm
Locking mechanism		Droplock® installation system <sup>1</sup>
Surface treatment		K-Guard+ PU coating
Guarantee <sup>2</sup>	Commercial Residential	15 years Lifetime guarantee
 Bevelled edge		Micro
 Mass per unit area	EN ISO 23997	8860 g/m <sup>2</sup>
 Standards	ISO 20326	Pass
 Classification	ISO 10874 - Commercial ISO 10874 - Domestic	33: Commercial heavy 23: Domestic heavy
 Reaction to fire	EN 13501-1	B <sub>fl</sub> -S <sub>1</sub>
 Staining resistance	EN ISO 26987/EN 423	Excellent
 Light fastness	EN ISO 105-B02	Pass (≥6)
Locking strength	EN ISO 20326 Annex D	Pass (≥ 2.0 kN/m)
 Furniture chair leg	EN ISO 16581	Pass (no visible damage)
 Acoustic impact noise reduction	EN ISO 10140-1:2016	ΔL <sub>w</sub> = 17db
 Indentation - residual	ISO 24343-1	Pass (≤0.1mm)
 Castor chair continuous use	ISO 4918	Pass (25,000 cycles)
 Thermal resistance	EN 12664	0.074 m <sup>2</sup> K/W Suitable for underfloor heating. Max 27 °C
 Slip resistance <sup>3</sup>	EN 13893 DIN 51130	DS R10
 Light Reflectance Value (LRV)	BS 8493:2008+A1:2010	See separate table
 Adhesive		None Required, Please install according to our installation instructions.
 Environmental	Indoor Air Comfort  ISO 14001 / ISO 9001	Gold Certification; Compliant low emitting VOC emissions.  Manufactured to quality and environment management systems standard
 Recycling		Suitable
 Phthalate free		Yes

<sup>1</sup> Droplock® is a patented technology invented by i4F Licensing nv, utilising proprietary 3L Triplelock and i4F Technology patents: [www.i4f-patents.com](http://www.i4f-patents.com)

<sup>2</sup> Subject to terms. Please see our website.

<sup>3</sup> Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

UK: 01386 820104 | ROI: 01 6569887

Email: [commercial@karndean.co.uk](mailto:commercial@karndean.co.uk)

Visit: [www.karndean.com](http://www.karndean.com)



Sep 23



EN 14041:2004 (DOP 2022/KREG/EN/01)
Approved body 1611
Floor Coverings (internal)
ISO 10874 Class 33
Manufactured to ISO 20326



EN 14041:2004 (DOP 2022/UKCA/KREG/01)
Approved body 0321
Floor Coverings (internal)
ISO 10874 Class 33
Manufactured to ISO 20326





	Product Code	Size		Box Quantity		Slip Resistance DIN 51130	LRV
		mm	inches	m <sup>2</sup>	Pieces		
Wood Designs	RKP9001	1510.0mm x 220.0mm	59.45" x 8.66"	1.994	6	R10	42
	RKP9002	1510.0mm x 220.0mm	59.45" x 8.66"	1.994	6	R10	37
	RKP9003	1510.0mm x 220.0mm	59.45" x 8.66"	1.994	6	R10	27
	RKP9004	1510.0mm x 220.0mm	59.45" x 8.66"	1.994	6	R10	27
	RKP9005	1510.0mm x 220.0mm	59.45" x 8.66"	1.994	6	R10	23
	RKP9006	1510.0mm x 220.0mm	59.45" x 8.66"	1.994	6	R10	13
	SM-RKP9001	720.1mm x 119.9mm	28.35" x 4.72"	2.073	24	R10	42
	SM-RKP9002	720.1mm x 119.9mm	28.35" x 4.72"	2.073	24	R10	37
	SM-RKP9003	720.1mm x 119.9mm	28.35" x 4.72"	2.073	24	R10	27
	SM-RKP9004	720.1mm x 119.9mm	28.35" x 4.72"	2.073	24	R10	27
	SM-RKP9005	720.1mm x 119.9mm	28.35" x 4.72"	2.073	24	R10	23
	SM-RKP9006	720.1mm x 119.9mm	28.35" x 4.72"	2.073	24	R10	13
	CL-RKP9001	1074.9mm x 214.9mm	42.32" x 8.46"	1.848	8	R10	42
	CL-RKP9002	1074.9mm x 214.9mm	42.32" x 8.46"	1.848	8	R10	37
	CL-RKP9003	1074.9mm x 214.9mm	42.32" x 8.46"	1.848	8	R10	27
	CL-RKP9004	1074.9mm x 214.9mm	42.32" x 8.46"	1.848	8	R10	27
	CL-RKP9005	1074.9mm x 214.9mm	42.32" x 8.46"	1.848	8	R10	23
	CL-RKP9006	1074.9mm x 214.9mm	42.32" x 8.46"	1.848	8	R10	13
	CP-RKP9001	938.5mm x 305.1mm	36.95" x 12.01"	1.719	6	R10	42
	CP-RKP9002	938.5mm x 305.1mm	36.95" x 12.01"	1.719	6	R10	37
	CP-RKP9003	938.5mm x 305.1mm	36.95" x 12.01"	1.719	6	R10	27
	CP-RKP9004	938.5mm x 305.1mm	36.95" x 12.01"	1.719	6	R10	27
	CP-RKP9005	938.5mm x 305.1mm	36.95" x 12.01"	1.719	6	R10	23
	CP-RKP9006	938.5mm x 305.1mm	36.95" x 12.01"	1.719	6	R10	13